

## EXPANDED ALUMINIUM MESH

**AluMesh**<sup>®</sup>  
CLEAN SAFE GUTTERS



### TECHNICAL SPECIFICATIONS

Material	Exposure Grade Virgin Aluminium	
Aperture Shape	Expanded – Diamond Shape	
Aperture Size	3.5 mm x 3.5 mm	
Wire Diameter	0.7 mm	
Material Thickness	0.5 mm	
Mesh Weight	500 g/sm.	
Roll Weight	15 kgs (after coating)	
Standard Mesh Widths	250, 500, 750, 1000 mm (other widths upon request)	
Length	10m, 15m, 30m	
Powder Coating	Interpon D610 (UV Stabilized)	
Packaging	Cardboard centre cores + clear wrap	         
Colour Range	Basalt, Cottage Green, Deep Ocean, Dune, Gully, Headland Ironstone, Jasper, Manor Red, Monument, Pale Eucalypt Paperbark, Shale Grey, Surfmist, Vincent Brown, Wallaby Windspray, Woodland Grey, Zinalume (uncoated)	
Testing & Accreditation	CSIRO Flammability Index -Zero (0) AS1530.2 AWQC Water quality AS4020	
Guarantee	15 years	
Applications	Zinalume, Colorbond, Aluminium, Tile, Polycarbonate (Not Compatible with Stainless Steel or Galvanized)	



©Copyright Protected 2018 to Ultraguard. Copying or alteration of this information without written authorisation from UltraGuard is forbidden. Contents are strictly confidential and privileged. Information is to be used as a guide only. UltraGuard reserves the right to make changes without notice. The data contained in this publication are based on the knowledge available at the time of printing and may be subjected to amendments due to changes in the methods of testing and/or manufacturing. All dimensions and properties are reported as typical values.E&OE.

